

Tubular Heaters & Guards

Tubular Heaters







FEATURES

- ▶ Instant start
- Heater fitted with internal thermal cut-out to prevent Overheating, will reset as unit cools
- ▶ Wall fixings included, cable length 1M
- ► Safety Guards available for all heater sizes

| Product | TUBH1 | TUBH2 | TUBH3 | TUBH4 | TUBH5 | TUBH6 | |
|-----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|----------------------|--|
| Description | Tubular Heater - 1ft | Tubular Heater - 2ft | Tubular Heater - 3ft | Tubular Heater - 4ft | Tubular Heater - 5ft | Tubular Heater - 6ft | |
| Product Finish | White | | | | | | |
| Barcode | 5012739 628078 | 5012739 628085 | 5012739 628092 | 5012739 628108 | 5012739 634413 | 5012739 628115 | |
| IP Rating | IP44 | | | | | | |
| Voltage | 230V AC~ 50Hz | | | | | | |
| Max Wattage | 60W | 120W | 180W | 240W | 300W | 360W | |
| Main Housing Material | Steel | | | | | | |
| Product Weight | 503g | 1006g | 1509g | 2012g | 2515g | 3018g | |
| Product Dimensions | L308 x W55.4mm | L612 X W55.4mm | L904 x W55.4mm | L1221 x W55.4mm | L1519 x W55.4mm | L1823 x W55.4mm | |
| Guarantee | 1 Year | | | | | | |
| Conforms To | BS EN 60335 | | | | | | |









Tubular Heaters & Guards

Tubular Heaters with Thermostat Control







FEATURES

- ▶ Built-in adjustable thermostats -5°C min to 40°C max
- Instant start
- Heater fitted with internal thermal cut-out to prevent overheating, will reset as unit cools
- ▶ Wall fixings included, cable length 1M
- Safety Guards available for all heater sizes

| Product | тивнітн | TUBH2TH | тивнзтн | TUBH4TH | TUBH5TH | TUBH6TH | |
|-----------------------|---|---|---|---|---|---|--|
| Description | Tubular Heater with Thermostat - 1ft | Tubular Heater with Thermostat - 2ft | Tubular Heater with Thermostat - 3ft | Tubular Heater with Thermostat - 4ft | Tubular Heater with Thermostat - 5ft | Tubular Heater with Thermostat - 6ft | |
| Product Finish | White | | | | | | |
| Barcode | 5012739 643606 | 5012739 643613 | 5012739 643620 | 5012739 6643637 | 5012739 643644 | 5012739 643651 | |
| IP Rating | IP44 | | | | | | |
| Voltage | 230V AC~ 50Hz | | | | | | |
| Max Wattage | 60W | 120W | 180W | 240W | 300W | 360W | |
| Thermostatic Range | 5°C to 40°C | | | | | | |
| Main Housing Material | Steel | | | | | | |
| Product Weight | 505g | 1008g | 1511g | 2014g | 2517g | 3020g | |
| Product Dimensions | L308 x W55.4mm | L612 X W55.4mm | L904 x W55.4mm | L1221 x W55.4mm | L1519 x W55.4mm | L1823 x W55.4mm | |
| Guarantee | 1 Year | | | | | | |
| Conforms To | BS EN 60335 | | | | | | |





Tubular Heaters & Guards

Tubular Heaters Safety Guards

TECHNICAL DATA SHEET





FEATURES

- Easy to install
- Safety Guards available for all Tubular Heaters 1ft 6ft



Our tubular heater safety guards fit both types of tubular heaters with or without themostat

TECHNICAL INFO

| Product | TUBGIINN | TUBG21NN | TUBH31NN | TUBH41NN | TUBH51NN | TUBH61NN | |
|-----------------------|--|----------------------|----------------------|----------------------|----------------------|----------------------|--|
| Description | Tubular Heater Guard | Tubular Heater Guard | Tubular Heater Guard | Tubular Heater Guard | Tubular Heater Guard | Tubular Heater Guard | |
| | - 1ft for TUBH1TH | - 2ft for TUBH2TH | - 3ft for TUBH3TH | - 4ft for TUBH4TH | - 5ft for TUBH5TH | - 6ft for TUBH6TH | |
| | & TUBH1 | & TUBH2 | & TUBH3 | & TUBH4 | & TUBH5 | & TUBH6 | |
| Guard Dimensions (mm) | L400 x W190 | L700 x W190 | L1000 x W190 | L1300 x W190 | L1600 x W190 | L1900 x W190 | |
| | (inc fixing holes) | (inc fixing holes) | (inc fixing holes) | (inc fixing holes) | (inc fixing holes) | (inc fixing holes) | |
| Product Finish | White Powder Coated - Steel Construction | | | | | | |
| Barcode | 5012739 | 5012739 | 5012739 | 5012739 | 5012739 | 5012739 | |
| | 644214 | 644221 | 644238 | 644245 | 644252 | 644269 | |





